

Novaflex®

PVC Conduit Hose

Novaflex 143 PVC Conduit Hose

MSHA Flame Resistant

An excellent cable cover for the mining industry. Low cost, flexible and easy to install. Meets the requirements of MSHA 1C-14/2. Split lengthwise for simple installation.

Specifications

Tube: PVC

Cover: PVC

Length 50ft & 100ft

Temperature Range: -20°F (-29°C) to +120°F (+49°C)



Specification Chart

Part No.	I.D.	O.D.	Standard Length/ft	WT LBS/FT
143WL-01000-00	1	1.46	100	0.40
143WL-01500-00	1½	1.96	100	0.46
143WL-02000-00	2	2.46	50	0.50
143WL-02500-00	2½	2.96	50	0.58
143WL-03000-00	3	3.46	50	0.66
143WL-04000-00	4	3.38	50	0.89

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

04.2020

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905)686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk