

Novaflex®

Novaflex Coolant Hose

Novaflex 2019 Coolant Hose

Designed for heavy duty industrial or automotive coolant service. The 3 ply construction hose has a specially blended tube compound designed to resist heat and oil. Meets SAE J20-R1 (3 & 5 ply only).

Also available in hard wall construction with a corrugated cover, part number 2019BE-XXXX-06. Meets SAE J20R2-D1 92XR

Specifications

Tube: Black EPDM

Reinforcement: Plies of fabric

Cover: Black EPDM

Length: Available in 50 ft lengths.

Temperature Range: -40°F (-40°C) to +200°F (+93°C)



Specification Chart

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2019BE-06250-70	¾	1.00	3	130	0.34
2019BE-07500-70	¾	1.13	3	115	0.38
2019BE-08750-70	¾	1.25	3	100	0.42
2019BE-01000-70	1	1.38	3	90	0.46
2019BE-01125-70	1 ¼	1.50	3	80	0.50
2019BE-01225-70	1 ¼	1.38	3	75	0.55
2019BE-01312-70	1 ¾	1.75	3	70	0.59
2019BE-01375-70	1 ¾	1.69	3	70	0.57
2019BE-01500-70	1 ½	1.88	3	65	0.63
2019BE-01625-70	1 ¾	2.00	3	60	0.67
2019BE-01750-70	1 ¾	2.13	3	55	0.71
2019BE-01875-70	1 ¾	2.25	3	55	0.76
2019BE-02000-70	2	2.38	3	50	0.80
2019BE-02125-70	2 ¼	2.50	3	45	0.84
2019BE-02225-70	2 ¼	2.63	3	45	0.88

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2019BE-02375-70	2 ¾	2.75	3	40	0.92
2019BE-02500-70	2 ½	2.88	3	40	0.96
2019BE-02625-70	2 ¾	3.00	3	40	1.01
2019BE-02750-70	2 ¾	3.13	3	35	1.05
2019BE-02875-70	2 ¾	3.25	3	35	1.09
2019BE-03000-70	3	3.38	3	35	1.13
2019BE-03125-70	3 ¼	3.50	3	30	1.17
2019BE-03225-70	3 ¼	3.63	3	30	1.22
2019BE-03500-70	3 ½	3.88	3	30	1.30
2019BE-04000-70	4	4.38	3	25	1.47
2019BE-04500-70	4 ½	4.88	3	25	1.63
2019BE-04750-70	4 ¾	5.13	3	20	1.72
2019BE-05000-70	5	5.38	3	20	1.80
2019BE-05500-70	5 ½	5.88	3	20	1.97

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

05.2015

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905)686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk